

SPECIFICATION (50Hz)

| | |
|----------------------|------|
| Voltage (V) | 230 |
| Watt (No Load) (W) | 100 |
| Watt (Rated) (W) | 140 |
| Amps (No Load) (A) | 0.60 |
| Amps (Rated) (A) | 0.63 |
| Speed (rpm) | 1400 |
| Capacitor (μ F) | 4.0 |
| Noise (dbA) | 49 |
| Net Weight (Kg) | 3.0 |

*Material :

*Rotor: Aluminum Die cast with Powder coated

*Type of protection: IP-54

*Insulation Class: "F"- Class

*Bearing: Maintenance free Ball Bearing.

*Motor Protection: Thermal Protected

*Permissible ambient temperature: 0 to 60° C

*High Voltage test according to IS: 3588-1987


*Cable length: 1.5 Sq.mm - 6 Core Wire, 600mm

*Balancing Grade: Fans conform 6.3 Grade as recommended by IS 1940-1-2003

*Direction of rotation: Sucking- Counter clockwise

Blowing- Clockwise, Seen on rotor

*Wiring Diagram :



MODEL : M0102-4E-K3

SCALE: NTS Page 1 of 1

REV/DATE: 00,26.03.2021

PREPARED BY : J.G.P

CHECKED BY : S.B.D

